

# Screen 6

Three-way system

## features


- ▶ Three-way design
- ▶ THX™ approved
- ▶ Very low distortion mid-range
- ▶ Full pattern control to 300Hz
- ▶ 90° x 50° dispersion

## applications

- ▶ Behind screen placement
- ▶ Premier/Showcase cinemas

The Screen 6 full-range system has been developed for use in large to very large-scale cinema environments. The system consists of a 4 x 15" (380mm) low frequency section plus a unique mid-range unit and high frequency horn which exhibits ideal pattern control across its operating range from 300Hz-20kHz. The Screen 6 is approved by Lucasfilm for use in category 3 (over 80ft in length or over 180000ft<sup>3</sup> in volume) THX theatres.

## overall dimensions



cinema

## technical specifications

TYPE	Three-way tri-amp screen system
FREQUENCY RESPONSE (1)	45Hz-20kHz ± 3dB
DRIVERS	4 x 15" (380mm) bass driver 6.5" (165mm) mid driver 1" (25mm) exit compression driver
RATED POWER (2)	LF: 1600W AES, 6400W peak MF: 150W AES, 600W peak HF: 60W AES, 240 peak
SENSITIVITY (3)	LF: 103dB MF: 107dB HF: 110dB
NOMINAL IMPEDANCE	LF: 2 x 4 ohms MF: 8 ohms HF: 8 ohms
DISPERSION (-6dB)	90° horizontal, 50° vertical
CROSSOVER	420Hz active, 2kHz active
ENCLOSURE	Vented
FINISH	Matt black
CONNECTORS	Binding Posts
DIMENSIONS	LF: (W) 1340mm x (H) 1010mm x (D) 470mm (W) 52.8ins x (H) 39.8ins x (D) 18.5ins MF/HF: (W) 715mm x (H) 885mm x (D) 610mm (W) 28.1ins x (H) 34.8ins x (D) 24ins
WEIGHT	LF: 2 x 61kg (134.5lbs) MF/HF: 18kg (39.6lbs)



approved by Lucasfilm for use in THX™ theatres.

Century Point, Halifax Road, Cressex Business Park,  
High Wycombe, Buckinghamshire HP12 3SL, England.  
Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669  
E-mail: [info@martin-audio.com](mailto:info@martin-audio.com)  
All information is Copyright © 2003 Martin Audio Ltd.



[www.martin-audio.com](http://www.martin-audio.com)